

UNIQUE PORTABLE DESIGN WITH HUGE LOAD CARRYING CAPACITY

200 kg Approved Load Rating Unsurpassed Performance and Reliability

We set our design engineers a goal that was previously thought to be unachievable. The amazing test results exceeded all our expectations and is a testament to the dedicated team of professionals at Eurogreen who accomplished this stunning outcome.

The level of comfort is equal to any road class scooter regardless of the passenger weight and the manoeuvrability in confined spaces is astounding.

The **Sumo** has raised the bench mark for high capacity portable scooter design and now provides a safe affordable transport means for those needing a substantial load rating and lightweight portable design.



US PAT 8,876,125 & PAT PEND.

Made In Taiwan





Specifications		
Number of Wheels		
Front Wheel Size		
Rear Wheel Size	200 x 6	

Specifications	SUMO	SUMO SP
Number of Wheels	4	
Front Wheel Size	200 x 65 mm (8 x 2.5")	
Rear Wheel Size	200 x 65 mm (8 x 2.5")	260 x 85 mm (10 x 3")
Ground Clearance(tiller)	65 mm (2.6")	
Length	1110 mm (43.7")	1130 mm (44.5")
Width	630 mm (24.8")	660 mm (26")
Weight Without Seat	Front frame: 13 kg (28.6 lbs)	
	Front frame without front wheels: 10.8 kg (23.8 lbs)	
	Back frame : 11.6 kg (25.5 lbs)	Back frame : 12.7 kg (28 lbs)
Weight of Seat	10.6 kgs (23.3 lbs incl. seat frame & arm rest)	
Max Loading	200 kg (440 lbs) on level ground	
Turn Radius	1000 mm (39.4")	
Motor Output	2 x 180W	
Transmission	Worm Drive Gearbox	
Reverse	Forward/Reverse Switch	
Brakes	Dynamic Braking and Electromagnetic Brake	
Battery (SLA)	24V 15 ah- 9.2kg (20 lbs)	
Lithium Battery (Optional)	24V 15ah- 4.0 kgs (9 lbs)	
Charger (SLA battery)	Off board 24 volt 2 amp	
Charger (Lithium battery)	Off board 24 volt 4 amp	
Max Speed	6.2 kph (3.9 mph)	8.2 kph (5 mph)
	(2nd speed choice 3.7 Kph -2.3 mph)	(2nd speed choice 4.8 Kph - 3 mph)
Slope Grade Ability	175 KG - 6 degree, 200 KG - 4 Degrees (Max).	
Travel Distance	Up to 10 km (6.2 miles) with standard SLA battery,	
	Up to 13 km (8 miles) with 15ah lithium battery	
Arm Rests Distance between		s 45cm - 57cm (18 -22.4")



